

# 7" CAPACITIVE CONTROL-PANEL



## DISPLAY

Display Size [inch]	7.0
Resolution	800 x 480
Contrast	500 CR
Brightness [cd/m <sup>2</sup> ]	450

## CENTRAL UNIT

CPU	AM6232 @ 2x 1,4 GHz
RAM Size	1 GB
Flash	8 GB eMMC
RTC	Supercap, approx. 14d
OS	RT Linux
Ethernet	2 x RJ45 10/100 Mbits
USB	1 x USB 2.0, Host, Typ A 1 x USB 2.0, OTG, Type C (device power)
Flash drives	microSD
CAN (optional)	1x CAN 2 a/b with internal 120Ω resistor

## ENVIRONMENTAL CONDITIONS

Operation Temp.	-10°C to 50°C
Storage Temp.	-20°C to 85°C
Humidity Range	10% to 90%

## CHASSIS

Case Material	Aluminium (Front panel material) Plastic (Housing material)
IP Protection	IP55 Front / IP20 Back
Case size L x W x H [mm]	182.0 x 116.0 x 37.0

## POWER

Power Supply	24 VDC
--------------	--------

## WEIGHT & PACKAGING

Net Weight	~0.5 kg est.
Gross Weight	~1.2 kg est. (incl. Cartonage)
Packaging Material	100% recyclable cardboard
Packaging Size L x W x H [mm]	200.0 x 160.0 x 60.0



4WEB-Automation GmbH  
Heisinger Straße 12  
87437 Kempten  
Germany

Tel: +49 (0)831 52622-336  
Fax: +49 (0)831 52622-682  
E-Mail: [info@4web-automation.de](mailto:info@4web-automation.de)  
Web: [www.4web-automation.de](http://www.4web-automation.de)