

10.1" CAPACITIVE TOUCH-PC

DISPLAY

Display Size [inch]	10.1
Aspect Ratio	16:10
Resolution	1280 × 800
Active Area [mm]	216.96 × 135.60
Brightness [cd/m ²]	1000+
Contrast Ratio	1000:1
LED life time [h]	100000
Viewing Angle [°]	170 / 170
Display Interface	LVDS

PC/MONITOR SYSTEM

Processor	Intel Atom® x6211E (Elkhart Lake)
Standard Operating System	Debian 12
OS available on request (additional fee)	Linux Ubuntu 22.4, Windows 11
RAM Size	8 GB DDR4
SSD Size	120 GB
Loudspeaker	2 x 2W
Wifi	Intel® AC 3168
Ambiente Light Sensor	1
HDMI	1
DP	1
Audio In / Out	1 (Realtek® ALC897 Audio CODEC)
USB 2.0	2
USB 3.2	2
Ethernet Network (10/100/1000 Mbit/s)	2 Realtek® 8111H (LAN 1 PoE option, LAN 2)
Serial Port RS232 (RX / TX only)	2
SD Card Slot	1
SIM Card Slot	1

TOUCH PANEL

Touch Type	Projected Capacitive 10-point Multi-touch
Printing Type	Ceramic
Glass Thickness [mm]	2.0
Cover Glass Surface Treatment	AG
IK Protection	IK08
Printing Color	RAL9004 (Black)
Strengthening	Thermally Strengthened
Touch Controller	EXC81W60
Touch Interface	USB

ENVIRONMENTAL CONDITIONS

Operation Temp.	-10°C to 60°C
Storage Temp.	-20°C to 70°C
Humidity Range	10% to 90%

CERTIFICATIONS

CE Certificate	Yes
FCC Certificate	Yes

CHASSIS

Case Design	SS-IP65
IP Protection	Full IP65
Case Color	Silver
Case Finish	Brushed
Case Material	Stainless Steel
Case size L × W × H [mm]	272.8 × 214.4 × 62.7
Mounting	VESA 100 × 100

ACCESSORIES

Power Adapter	100-240V ACDC active switching; 12V DC-Out
Wifi Antenna	Yes
Short Instruction manual	Yes

POWER

Power Indicator	Green LED
Working Power	9 - 36 V
Power Consumption	27W
Stand-By Consumption	<1.2W

WEIGHT & PACKAGING

Net Weight	~3.1 kg est.
Gross Weight	~4.2 kg est. (incl. Cartonage)
Packaging Material	100% recyclable cardboard and polyethylene (PE)
Packaging Size L × W × H [mm]	433.0 × 290.0 × 80.0