

21.5" CAPACITIVE TOUCH-PC

DISPLAY

Display Size [inch]	21.5
Aspect Ratio	16:9
Resolution	1920 × 1080
Active Area [mm]	476.06 × 267.78
Brightness [cd/m ²]	1000+
Contrast Ratio	1000:1
LED life time [h]	100000
Viewing Angle [°]	150 / 178
Display Interface	LVDS

PC/MONITOR SYSTEM

Processor	Intel Atom® x6211E (Elkhart Lake)
Standard Operating System	Debian 12
OS available on request (additional fee)	Linux Ubuntu 22.4, Windows 11
RAM Size	8 GB DDR4
SSD Size	120 GB
Loudspeaker	2 x 2W
Wifi	Intel® AC 3168
Ambiente Light Sensor	1
IP69K 9-36V DC-IN connector (M12, 4 pin)	1
IP69K LAN connector (M12, 8 pin)	1
IP69K COM connector (M12, 4 pin)	1

TOUCH PANEL

Touch Type	Projected Capacitive 10-point Multi-touch
Printing Type	Ceramic
Glass Thickness [mm]	2.0
Cover Glass Surface Treatment	AG
IK Protection	IK08
Printing Color	RAL9004 (Black)
Strengthening	Thermally Strengthened
Touch Controller	EXC81W84
Touch Interface	USB

ENVIRONMENTAL CONDITIONS

Operation Temp.	-10°C to 60°C
Storage Temp.	-20°C to 70°C
Humidity Range	10% to 90%

CERTIFICATIONS

CE Certificate	Yes
FCC Certificate	Yes

CHASSIS

Case Design	SS-IP69K
IP Protection	Full IP69K
Case Color	Silver
Case Finish	Brushed
Case Material	Stainless Steel
Case size L × W × H [mm]	527.3 × 214.4 × 62.7
Mounting	VESA 100 × 100

ACCESSORIES

Power Adapter & DC-In IP69K Cable	Yes
Wifi Antenna	Yes
Short Instruction manual	Yes

POWER

Power Indicator	Green LED
Working Power	9 - 36 V
Power Consumption	64W
Stand-By Consumption	<1.2W

WEIGHT & PACKAGING

Net Weight	~10.3 kg est.
Gross Weight	~10.8 kg est. (incl. Cartonage)
Packaging Material	100% recyclable cardboard and polyethylene (PE)
Packaging Size L × W × H [mm]	700.0 × 430.0 × 110.0