

# 24.0" CAPACITIVE TOUCH-PC

## DISPLAY

Display Size [inch]	23.8
Aspect Ratio	16:9
Resolution	1920 × 1080
Active Area [mm]	527.04 × 296.46
Brightness [cd/m <sup>2</sup> ]	500
Contrast Ratio	3000:1
LED life time [h]	30000
Viewing Angle [°]	178 / 178
Display Interface	LVDS

## PC/MONITOR SYSTEM

Processor	Intel Atom® x6413E (Elkhart Lake)
Standard Operating System	Debian 12
OS available on request (additional fee)	Linux Ubuntu 22.4, Windows 11
RAM Size	8 GB DDR4
SSD Size	120 GB
Loudspeaker	2 x 2W
Wifi	Intel® AC 3168
HDMI	1
DP	1
Audio In / Out	1 (Realtek® ALC897 Audio CODEC)
USB 2.0	2
USB 3.2	2
Ethernet Network (10/100/1000 Mbit/s)	2 Realtek® 8111H (LAN 1 PoE option, LAN 2)
Serial Port RS232 (RX / TX only)	2
SD Card Slot	1
SIM Card Slot	1

## TOUCH PANEL

Touch Type	Projected Capacitive 10-point Multi-touch
Printing Type	Organic
Glass Thickness [mm]	1.1
Cover Glass Surface Treatment	AG
IK Protection	IK08
Printing Color	RAL9004 (Black)
Strengthening	Thermally Strengthened
Touch Controller	EXC81W84
Touch Interface	USB

## ENVIRONMENTAL CONDITIONS

Operation Temp.	-10°C to 60°C
Storage Temp.	-20°C to 70°C
Humidity Range	10% to 90%

## CERTIFICATIONS

CE Certificate	Yes
FCC Certificate	Yes

## CHASSIS

Case Design	Rubber Frame Sealing
IP Protection	IP65 Front / IP40 Back
Case Color	RAL9004 (Black)
Case Coating	Powder Coating
Case Material	Aluminum
Case size L × W × H [mm]	579.4 × 347.0 × 51.5
Cut-out for clamp supports L × H [mm]	555.4 × 323.0
Max. wall thickness for clamp supports [mm]	5.0
Amount of clamps required	7
Mounting	VESA 100 × 100

## ACCESSORIES

Power Adapter	100-240V ACDC active switching; 12V DC-Out
Wifi Antenna	Yes
Short Instruction manual	Yes

## POWER

Power Indicator	Green LED
Working Power	9 - 36 V
Power Consumption	31.3W
Stand-By Consumption	<1W

## WEIGHT & PACKAGING

Net Weight	~6.3 kg est.
Gross Weight	~9.5 kg est. (incl. Cartonage)
Packaging Material	100% recyclable cardboard and polyethylene (PE)
Packaging Size L × W × H [mm]	735.0 × 425.0 × 80.0